

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Rust Master Primer
PRODUCT CODE: 80-350
RECOMMENDED USE: Rust Converter
RESTRICTIONS ON USE: None known.
COMPANY NAME: Kimball Midwest
COMPANY ADDRESS: 4800 Roberts Rd Columbus, OH 43228
COMPANY PHONE: 800-233-1294
EMERGENCY PHONE: Chemtrec: 800-424-9300

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Gases Under Pressure: Liquefied Gas

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Specific Target Organ Toxicity (Repeated Exposure): Category 2

HAZARD STATEMENT(S): DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Do not breathe mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	30-40%
N-Butane	106-97-8	20-30%
Isopropyl alcohol	67-63-0	10-20%
Propane	74-98-6	5-15%
2-Butoxyethanol	111-76-2	5-15%
Diethylene glycol	111-46-6	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

Safety Data Sheet

SKIN: Wash skin thoroughly with soap and water. Remove contaminated clothing and shoes, launder before reuse. If irritation persists seek medical attention.

ACUTE HEALTH HAZARDS: Causes eye irritation including redness, tearing, and pain. Prolonged contact with skin may cause irritation. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS: Respiratory disease and dermal related medical conditions. Kidney and liver damage possible.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed toward the control of symptoms and the clinical condition.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Vapors may form explosive mixtures with air. Vapors heavier than air will settle in low lying areas and may travel to source of ignition and flash back. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Material is heavier than air and can settle in low lying areas in flammable concentrations. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains, and natural waterways. Place waste in proper containers for disposal. U.S. regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the U.S. Coast Guard National Response Center is (800) 424-8802.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state and local regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Keep away from heat, open flames, or other sources of ignition. Avoid contact with skin, eyes and clothing. Wear appropriate protective equipment. Do not inhale mist or vapor. Store in a cool, dry area. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	250 ppm
N-Butane	Not Established	1000 ppm
Isopropyl alcohol	400 ppm	200 ppm
Propane	1000 ppm	1000 ppm
2-Butoxyethanol	50 ppm	20 ppm
Diethylene glycol	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves.

Safety Data Sheet

ADDITIONAL MEASURES: Avoid contact with skin or eyes and avoid breathing vapors. Wash hands after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear to hazy brown spray
ODOR: Acetone odor
ODOR THRESHOLD: N/D
pH: N/D
MELTING POINT/FREEZING POINT: N/D
INITIAL BOILING POINT AND BOILING RANGE: N/D
FLASH POINT: N/D
EVAPORATION RATE: N/D
FLAMMABILITY(solid/gas): Extremely Flammable Aerosol
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:
 LOWER FLAMMABILITY LIMIT: N/D
 UPPER FLAMMABILITY LIMIT: N/D
 EXPLOSIVE LIMIT LOWER (%): N/D
 EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H₂O=1): 0.82 - 0.88 @ 77 °F (25 °C)
SOLUBILITY(IES): N/D
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.
CHEMICAL STABILITY: Stable.
POSSIBLE HAZARDOUS REACTIONS: None known.
CONDITIONS TO AVOID: Temperatures greater than 122 °F and sources of ignition. Avoid use in confined areas. Avoid incompatibles.
INCOMPATIBLE MATERIALS: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Acetone** (67-64-1): LD₅₀ (Oral, Rat) 5800 mg/kg; LD₅₀ (Dermal, Rabbit) 5000 mg/kg; LC₅₀ (Inhalation, Rat, 4hr) 20 mg/L. **n-Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³. **Isopropyl alcohol** (67-63-0): LD₅₀ (Oral, Rat) 5045 mg/kg; LD₅₀ (Dermal, Rabbit) 12870mg/kg; LC₅₀ (Inhalation, Rat, 4h) 78.6 mg/L. **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **2-Butoxyethanol** (111-76-2): LD₅₀ (Oral, Rat) 320 mg/kg; LD₅₀ (Dermal, Rabbit) 440 mg/kg; LC₅₀ (Inhalation, Mice, 4h) 700 ppm. **Diethylene glycol** (111-46-6): LD₅₀ (Oral, Rat) 25,300 mg/kg; LD₅₀ (Oral, Human) 1,000 mg/kg; LD₅₀ (Dermal, Rabbit) 12,500 mg/kg; LC₅₀ (Inhalation, Rat) > 1,172 ppm.
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Redness, irritation, causes temporary corneal opacity.
INGESTION: May cause gastrointestinal irritation, nausea, vomiting, dizziness.
INHALATION: May cause dizziness, nausea, central nervous system effects.
SKIN: May cause irritation, redness, and dermatitis.
MEDICAL CONDITION AGGRAVATED: Pre-existing skin and respiratory disorders.
ACUTE HEALTH HAZARDS: Causes eye irritation including redness, tearing, and pain. Prolonged contact with skin may cause irritation. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
CHRONIC HEALTH HAZARDS: Respiratory disease and dermal related medical conditions. Kidney and liver damage possible.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

Safety Data Sheet

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: **Acetone** (67-64-1): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC₅₀ (*Daphnia magna*, 48h) 6100 mg/L; EC₅₀ (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC₅₀ (*Psuedomonas putida*, 16h) 1700 mg/L. **Isopropyl alcohol** (67-63-0): LC₅₀ (Fish, 96h): > 100 mg/L; LC₅₀ (Fathead minnow, 96h) 9640 mg/L; EC₅₀ (*Daphnia*, 24h) 5102 mg/L. **Diethylene glycol** (111-46-5): LC₅₀ (Bluegill sunfish) > 1000 mg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state and local regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Acetone** (67-64-1) Reportable Quantity = 5,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Flammable (gases, aerosols, liquids, solids). Gas under pressure. Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure).

SARA 313 REPORTABLE INGREDIENTS: None.

CLEAN WATER ACT: **Acetone** (67-64-1) is a hazardous substance.

STATE REGULATIONS: California Proposition 65: This product contains no known chemicals regulated by California Proposition 65. **Acetone** (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. **Isopropyl alcohol** (67-63-0): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CT, FL, IL, MN, NJ, PA, RI, TN. **2-Butoxyethanol** (111-76-2): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: PA, RI. **Diethylene glycol** (111-46-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: PA, RI.

INTERNATIONAL REGULATIONS: No information available.

VOLATILE ORGANIC COMPOUNDS (VOC): 51%

NFPA HEALTH: 1

NFPA FLAMMABILITY: 3

HMIS HEALTH: 1

HMIS FLAMMABILITY: 3

Safety Data Sheet

NFPA REACTIVITY: 0
NFPA OTHER: None

HMIS REACTIVITY: 0
HMIS PROTECTION: B

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Regulatory Affairs

DATE PREPARED: 07/05/2013

REVISION DATE: 09/10/2021

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.