

Safety Data Sheet ELECTRA COAT AEROSOL

Supersedes Date 12/16/2014

Issuing Date 12/28/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ELECTRA COAT AEROSOL

Recommended use Clear coating

Information on Manufacturer

CERTIFIED LABS, DIV. OF NCH CORP.

BOX 152170

IRVING, TEXAS 75015

Product Code 5687

Chemical nature Polymer suspension

Emergency Telephone Number

CHEMTREC® 800-424-9300

Telephone inquiry

972-579-2477

2. HAZARD IDENTIFICATION

Color Colorless - Light yellow

Physical state Liquid

Odor Petroleum distillates

GHS

Classification

Physical Hazards

Flammable Aerosols

Gases under pressure

Category 1

Compressed Gas

Health Hazard

Acute Inhalation Toxicity - Gas

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Reproductive Toxicity

Specific target organ systemic toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

Category 4

Category 2

Category 2A

Category 2

Category 3

Category 2

Other hazards

None

Labeling

Signal Word

DANGER



Hazard statements

H222 - Extremely flammable aerosol

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, sparks, open flames or hot surfaces.

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe vapor, mist or gas

P271 - Use in a well-ventilated area.

P280 - Wear protective gloves, protective clothing and eye protection.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a physician if unwell.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P332 + P313 - If skin irritation occurs, get medical attention.

P362 - Take off contaminated clothing and wash before reuse.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists, get medical attention.

P308 + P313 - IF exposed or concerned, get medical attention

P403 - Store in a well-ventilated place.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents and container in accordance with applicable local regulations.

17 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %
Xylenes (o-, m-, p- isomers)	1330-20-7	15-40
Hexanes	110-54-3	15-40
Petroleum gases, liquified, sweetened	68476-86-8	15-40
Styrene-butadiene polymer	9003-55-8	10-30

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wipe up with absorbent material (e.g. cloth, fleece). Wash off with soap and plenty of water. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Inhalation	Move to fresh air. In case of shortness of breath, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if irritation develops and persists.
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point -136 °F / -93 °C	Method Seta closed cup	
Flammability Limits in Air %: Solvent mixture.	Upper: 9.5	Lower: 0.9
Suitable Extinguishing Media		
Foam. Dry chemical. Water spray. Carbon dioxide (CO ₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical		
Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >30 inches / >75 cm and Burnback: 6 inch / 15 cm.		
Protective Equipment and Precautions for Firefighters		
As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) - 3		
NFPA	Health 2	Flammability 4
HMIS	Health 2	Flammability 4
		Instability 0
		Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Take precautionary measures against static discharges. Remove all sources of ignition. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.				
Storage	Keep away from heat and sources of ignition. Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.				
Storage Temperature	Minimum	35 °F / 2 °C		Maximum	130 °F / 54 °C
Storage Conditions	Indoor	X	Outdoor	Heated	Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³	No data available
Hexanes	TWA: 50 ppm Skin	TWA: 500 ppm TWA: 1800 mg/m ³	1100 ppm TWA: 50 ppm TWA: 180 mg/m ³
Styrene-butadiene polymer	3 mg/m ³ PNOS	5 mg/m ³ PNOR	No data available

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin Protection

Wear suitable protective clothing, Impervious gloves.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Viscosity	Semi-viscous
Color	Colorless - Light yellow	Odor	Petroleum distillates
Odor Threshold	Not applicable	Appearance	Transparent - Hazy
pH	Not applicable	Specific Gravity	0.77
Evaporation Rate	>1	Percent Volatile (Volume)	0
VOC Content (%)	83	VOC Content (g/L)	639
Vapor Pressure	No information available	Vapor Density	>1 (Air = 1.0)
Solubility	Negligible	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition Temperature	No data available
Boiling Point/Range	No data available	Flammability (solid, gas)	No data available
Flash Point	-136 °F / -93 °C	Method	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Solvent mixture	Upper: 9.5 Lower: 0.9	

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition.
Incompatible Products	Strong oxidizing agents.
Decomposition Temperature	No data available
Hazardous Decomposition Products	Carbon oxides.
Possibility of Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 No information available

Dermal LD50 No information available

Inhalation LC50

Gas No information available

Mist No information available

Vapor No information available

Principle Route of Exposure

Skin contact, Inhalation, Eye contact.

Primary Routes of Entry

Skin contact, Skin Absorption, Inhalation.

Acute Effects:

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

Inhalation Causes respiratory tract irritation. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity

Repeated and prolonged exposure to solvents may cause brain and nervous system damage. May cause irregular heartbeats, especially under conditions of stress. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Suspect reproductive hazard - contains material which may injure unborn child.

Target Organ Effects

Eyes, Skin, Respiratory system, Central nervous system.

Aggravated Medical Conditions

Skin disorders, Respiratory disorders, Neurological disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Xylenes (o-, m-, p- isomers) 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h	No data available	No data available
Hexanes 110-54-3	= 15000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h	No data available	No data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Hexanes 110-54-3	No data available	No data available	No data available	X	Skin; Central nervous system; Eyes; Respiratory system

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA	Other
Xylenes (o-, m-, p- isomers) 1330-20-7	A4	Group 3	not applicable	not applicable	not applicable
Styrene-butadiene polymer 9003-55-8	not applicable	Group 3	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	Partition coefficient
Xylenes (o-, m-, p- isomers)	EC50 = 11 mg/L Pseudokirchneriella subcapitata 72 h	LC50 = 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50 = 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50 = 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50	3.15
Hexanes	No information available.	LC50 2.1 - 2.98 mg/L Pimephales promelas 96 h	No information available	No information available.	N/A
Petroleum gases, liquified, sweetened	No information available.	No information available.	No information available	No information available.	2.8

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations.

Container Disposal

Contents under pressure. Do not puncture. Empty containers should be taken for local recycling, recovery, or waste disposal. Empty remaining contents.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name
Hazard Class
Description

CONSUMER COMMODITY
ORM-D
CONSUMER COMMODITY,ORM-D

TDG

Proper shipping name

Aerosols

Hazard Class 2.1
UN-No UN1950
Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO

UN-No UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Shipping Description UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

IATA

UN-No UN1950
Proper Shipping Name AEROSOLS, FLAMMABLE
Hazard Class 2.1
ERG-Code 10L
Shipping Description UN1950, AEROSOLS, FLAMMABLE,2.1, LTD QTY

IMDG/IMO

Proper Shipping Name AEROSOLS
Hazard Class 2.1
UN-No UN1950
EmS No. F-D, S-U
Description UN1950, AEROSOLS,2.1, LTD QTY

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Component	CAS No.	Weight %	SARA 313 - Threshold Values
Hexanes	110-54-3	15-40	1.0
Xylenes (o-, m-, p- isomers)	1330-20-7	15-40	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Xylenes (o-, m-, p- isomers)	100 lb	Not applicable
Hexanes	5000 lb	Not applicable

16. OTHER INFORMATION

Prepared By Samantha Purvis
Supersedes Date 12/16/2014
Issuing Date 12/28/2016
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.