

**SAFETY DATA SHEET****Torque-Lok™ High Strength Threadlocker**

Version 1.2

Revision Date 04/01/2021

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Torque-Lok™ High Strength Threadlocker  
Product code : 80-144 and 80-145

**Manufacturer or supplier's details**

Company : Kimball Midwest  
4800 Roberts Road  
Address : Columbus, OH  
43228  
Telephone : 800.233.1294

Emergency Phone Number (CHEMTREC): 1-800-424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Anaerobic Cure Adhesive  
Restrictions on use : For industrial use only.

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	liquid
Color	red
Odor	characteristic

**GHS Classification**

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)  
Specific target organ toxicity - repeated exposure : Category 2

**GHS label elements**

Hazard pictograms :



Signal Word : Warning

**Hazard Statements:**

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary Statements:

**Prevention:** P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

**Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

#### Potential Health Effects

#### Carcinogenicity:

##### IARC

Group 2B: Possibly carcinogenic to humans  
cumene 98-82-8

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### NTP

Reasonably anticipated to be a human carcinogen  
cumene 98-82-8

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Poly(oxy-1,2-ethanediyl), .alpha.-(2-methyl-1-oxo-2-propenyl)-.omega.-[(2-methyl-1-oxo-2-propenyl)oxy]-	25852-47-5	30 - 50
methacrylic acid, monoester with propane-1,2-diol	27813-02-1	10 - 20
α,α-dimethylbenzyl hydroperoxide	80-15-9	1 - 5
cumene	98-82-8	0.1 - 1
2'-phenylacetohydrazide	114-83-0	0.1 - 1

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

	attendance.
If inhaled	: Move to fresh air. Keep patient warm and at rest. Consult a physician after significant exposure.
In case of skin contact	: Wash off immediately with soap and plenty of water. Call a physician if irritation develops or persists.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids. Seek medical advice.
If swallowed	: If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice.

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: Water spray jet
Hazardous combustion products	: Nitrogen oxides (NOx) Sulfur oxides
Specific extinguishing methods	:
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation.
Environmental precautions	: Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	: Ventilate the area. Soak up with inert absorbent material. Shovel or sweep up.

#### SECTION 7. HANDLING AND STORAGE

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Wear personal protective equipment.  
Do not get on skin or clothing.  
Keep away from heat and flame.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.  
Store in original container.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL

##### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection  
Material : Neoprene gloves  
Nitrile rubber  
butyl-rubber
- Eye protection : Tightly fitting safety goggles  
Ensure that eyewash stations and safety showers are close to the workstation location.

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

---

Skin and body protection	: Long sleeved clothing Preventive skin protection
Protective measures	: Avoid contact with skin.
Hygiene measures	: Avoid contact with skin, eyes and clothing.

---

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: red
Odor	: characteristic
Odor Threshold	: No data available
Melting point/freezing point	: is not determined
Boiling point/boiling range	: is not determined
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Density	: 1.06 g/cm3
Solubility(ies)	
Water solubility	: is not determined
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: is not determined
Viscosity	
Viscosity, kinematic	: is not determined

---

#### SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Hazardous decomposition products	: Nitrogen oxides (NOx) Sulfur oxides

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Acute toxicity

Product:

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

#### **Components:**

##### **α,α-dimethylbenzyl hydroperoxide:**

Acute oral toxicity : LD50 Oral Rat: 382 mg/kg

Acute inhalation toxicity : LC50 Rat: 220 ppm  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal Rat: 500 mg/kg

##### **cumene:**

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

#### **Skin corrosion/irritation**

No data available

#### **Serious eye damage/eye irritation**

No data available

#### **Respiratory or skin sensitization**

No data available

#### **Germ cell mutagenicity**

No data available

#### **Carcinogenicity**

No data available

#### **Reproductive toxicity**

No data available

#### **STOT-single exposure**

No data available

#### **STOT-repeated exposure**

No data available

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

#### Aspiration toxicity

No data available

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### methacrylic acid, monoester with propane-1,2-diol :

Toxicity to fish : LC50 (Fish): 493 mg/l  
Exposure time: 48 h  
Test Method: static test

##### $\alpha,\alpha$ -dimethylbenzyl hydroperoxide :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l  
Exposure time: 96 h  
Test Method: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7 mg/l  
Exposure time: 24 h  
Test Method: static test

##### cumene :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l  
Exposure time: 96 h  
Test Method: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.6 mg/l  
Exposure time: 48 h  
Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 2.6 mg/l  
Exposure time: 72 h  
Test Type: flow-through test

#### Persistence and degradability

No data available

#### Bioaccumulative potential

#### Mobility in soil

No data available

#### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

#### Disposal methods

Waste from residues : Do not dispose of together with household waste.  
Do not dispose of waste into sewer.  
To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

## SECTION 14. TRANSPORT INFORMATION

#### Special precautions for user

Not applicable

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15. REGULATORY INFORMATION

#### SARA 311/312 Hazards

: Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

#### SARA 302

: This material does not contain any components with a section 302 EHS TPQ.



## SAFETY DATA SHEET

### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

#### SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

2-phenoxyethyl methacrylate	10595-06-9
1,2-benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2
$\alpha,\alpha$ -dimethylbenzyl hydroperoxide	80-15-9
cumene	98-82-8

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

2-phenoxyethyl methacrylate	10595-06-9
cumene	98-82-8

#### US State Regulations

##### California Prop 65

Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

##### TSCA

All substances listed as active on the TSCA inventory

**Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

## SECTION 16. OTHER INFORMATION

Prepared by: Regulatory Department

## SAFETY DATA SHEET


### Torque-Lok™ High Strength Threadlocker

Version 1.2

Revision Date 04/01/2021

#### Further information

##### NFPA:



##### HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.