

# Safety Data Sheet

Page 1 of 7

OSI HM270 Construction Silicone Sealant

SDS No.: 175013 V001.3 Date of issue: 02.06.2020

## Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** OSI HM270 Construction Silicone Sealant Intended use: Silicone sealant Supplier: Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia Phone: +61 (3) 9724 6444 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379 **Emergency information:** 

#### Section 2. Hazards identification

Classification of the substance or mixture Hazardous according to the criteria of Safe Work Australia.

#### **GHS Classification:**

Hazard Class Skin irritation Serious eye irritation

Hazard pictogram:

Signal word:

Hazard Category Category 2 Category 2



Danger

Hazard statement(s):	H315 Causes skin irritation. H319 Causes serious eye irritation.
Precautionary Statement(s): Prevention:	P264 Wash hands thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	<ul> <li>P302+P352 IF ON SKIN: Wash with plenty of water.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P332+P313 If skin irritation occurs: Get medical attention.</li> <li>P337+P313 If eye irritation persists: Get medical attention.</li> <li>P362 Take off contaminated clothing.</li> </ul>
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

## Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

# Section 3. Composition / information on ingredients

General chemical description:

Mixture resins Acetoxy curing silicone

**Identity of ingredients:** 

Type of preparation:

Chemical ingredients	CAS-No.	Proportion
Silicon dioxide	7631-86-9	< 10 %
Cyclosiloxanes, di-Me	69430-24-6	< 10 %
non hazardous ingredients~		< 85 %

	Section 4. First aid measures					
Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.					
Skin:	In case of contact, immediately remove contaminated clothing and flush skin with copious amounts of water. Seek medical advice.					
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.					
Inhalation:	Move to fresh air. Keep warm and in a quiet place. Seek medical advice.					
First Aid facilities:	Eye wash and safety shower Normal washroom facilities					

Medical attention and special treatment:

Treat symptomatically.

	Section 5. Fire fighting measures				
Suitable extinguishing media:	Carbon dioxide, foam, powder				
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide. Oxides of nitrogen. Formaldehyde				
Special protective equipment for fire-fighters:	Wear full protective clothing. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).				
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.				

Section 6. Accidental release measures					
Personal precautions:	Avoid contact with skin and eyes. Ensure adequate ventilation.				
	Wear protective equipment.				
Environmental precautions:	Do not let product enter drains.				
Clean-up methods:	Scrape up as much material as possible.				
	Ensure adequate ventilation.				
	Store in a partly filled, closed container until disposal.				
	Dispose of contaminated material as waste according to Section 13.				

Section 7. Handling and storage					
Precautions for safe handling:	Ensure that workrooms are adequately ventilated. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing, safety glasses and gloves.				
Conditions for safe storage:	Keep container tightly sealed. Do not store or use near heat, spark, open flame or other sources of ignition. Store in a cool, well-ventilated place.				

# Section 8. Exposure controls / personal protection

#### National exposure standards:

Ingredient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.	Peak Limit.	STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
OIL MIST, REFINED MINERAL			5				
64742-46-7							
ACETIC ACID						15	37
64-19-7							
ACETIC ACID		10	25				
64-19-7							

SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 7631-86-9	Respirable dust.		2				
FUMED SILICA (RESPIRABLE DUST) 7631-86-9	Respirable dust.		2				
Engineering controls:	Ensu	e good ventila	tion/extraction				
Eye protection:	For e	ye protection, i	use tightly fitte	d safety goggle	es and a face-s	hield	
Skin protection:	Wear suitable protective clothing. Protective gloves made of rubber.						
Respiratory protection:	If inh requi	alation risk exi rements of AS/	ists, wear a resp NZS 1715 and	pirator or air su AS/NZS 1716	ipplied mask c	omplying with	the

# Section 9. Physical and chemical properties

Appearance:	Clear to slightly hazy
Specific gravity:	1 01
Flash point:	$> 93 ^{\circ}C (> 199.4 ^{\circ}F)$
Lower explosive limit:	4 %(V)
Upper explosive limit:	19.9 %(V)
Vapor pressure: (; 20 °C (68 °F))	< 10 mm hg
Vapor density:	Heavier than air.
Density:	1.01 g/cm3
VOC content:	3.0 % 30 g/l
	Section 10. Stability and reactivity
Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Extremes of temperature. Humidity.
Incompatible materials:	Strong oxidizing agents. Polymerises in presence of water. Reaction with strong acids. Reaction with strong bases
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide. Oxides of nitrogen. At higher temperatures (>150C) may release formaldehyde (traces). Acetic acid is liberated slowly upon contact with moisture.

## Section 11. Toxicological information

Health Effects:	
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin:	Causes skin irritation.
	Symptoms may include redness, edema, drying, defatting and cracking of the skin.
	May cause skin sensitization.
Eyes:	Causes serious eye damage.
	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal
	injury. Symptoms may include discomfort or pain, excess blinking and tear production, with
	marked redness and swelling of the conjunctiva.
Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.

## Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Silicon dioxide	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7631-86-9	LC50	> 2.08 mg/l	inhalation	4 h	rat	Oral Toxicity)
	LD50	> 5,000 mg/kg	dermal		rabbit	OECD Guideline 403 (Acute
						Inhalation Toxicity)
						not specified
Cyclosiloxanes, di-Me 69430-24-6	LD50	> 2,400 mg/kg	dermal		rat	not specified

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Silicon dioxide 7631-86-9	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Silicon dioxide 7631-86-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

# Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Silicon dioxide	negative	bacterial reverse	with and without		OECD Guideline 471
7631-86-9	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
	negative	Ames test)	with and without		Assay)
		mammalian cell			OECD Guideline 476 (In vitro
		gene mutation assay			Mammalian Cell Gene
		in vitro mammalian			Mutation Test)
		chromosome			OECD Guideline 473 (In vitro
		aberration test			Mammalian Chromosome
					Aberration Test)
Silicon dioxide	negative	inhalation		rat	not specified
7631-86-9					

# Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Silicon dioxide 7631-86-9	NOAEL=> 4,000 - 4,500 mg/kg	oral: feed	13 weeksdaily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Silicon dioxide 7631-86-9	NOAEL=1.3 mg/m3	inhalation	13 w6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

#### General ecological information:

Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Silicon dioxide	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
7631-86-9					Danio rerio)	203 (Fish, Acute
	l l					Toxicity Test)
Silicon dioxide	EL50	> 1,000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline
7631-86-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Silicon dioxide	NOELR	10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
7631-86-9						201 (Alga, Growth
						Inhibition Test)
Silicon dioxide	EL50	> 10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
7631-86-9						201 (Alga, Growth
ann 11 11		10.000 1		<u> </u>		Inhibition Test)
Silicon dioxide	EC0	10,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 2/
7631-86-9						(Bacterial oxygen
	1.050	2 000 //	<b>F</b> 1	0.61	<b>.</b> ,	consumption test)
Cyclosiloxanes, di-Me	LC50	> 3,000  mg/l	Fish	96 h	Leuciscus idus	OECD Guideline
69430-24-6						203 (Fish, Acute
Contraitement di Ma	EC 50	× 10.000 ···· - /1	Destado	21		OECD Cuidaling
Cyclosiloxanes, di-Me	EC 50	> 10,000  mg/I	Bacteria	3 n		OECD Guideline
69430-24-6						209 (Activated
						Sludge, Respiration
			1	1		innibition lest)

#### Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Silicon dioxide 7631-86-9	0.53					QSAR (Quantitative Structure Activity
						Relationship)

# Section 13. Disposal considerations

Waste disposal of product:	Dispose of in accordance with local and national regulations.
Disposal for uncleaned package:	After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

# Section 14. Transport information

#### **Road and Rail Transport:**

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

#### Marine transport IMDG: Not dangerous goods

rtot dangerous goods

Air transport IATA: Not dangerous goods

	Section 15. Regulatory information
SUSMP Poisons Schedule	None
AICS:	All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).
	Section 16. Other information
Abbreviations/acronyms:	ADGC - Australian Dangerous Goods Code GHS: Globally Harmonized System CAS: Chemical Abstracts Service IMDG: International Maritime Dangerous Goods code IATA-DGR: International Air Transport Association – Dangerous Goods Regulations STEL - Short term exposure limit TWA - Time weighted average
Reason for issue:	Reviewed SDS. Reissued with new date. involved chapters: 1,2,3,16
Date of previous issue:	22.05.2015
Disclaimer:	The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.