



Revision Number: 005.0

Issue date: 08/31/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite® PL® Polyurethane Concrete Crack and Masonry Sealant
Product type: Sealant
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 1618522
Region: United States
Contact information:
 Telephone: (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE IRRITATION.
 TOXIC IF INHALED.
 MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.
 SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	3
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
CARCINOGENICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	10 - 30
Stoddard solvent, <0.1% Benzene	8052-41-3	1 - 5
Talc	14807-96-6	1 - 5
Calcium oxide	1305-78-8	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Toluene-2,6-diisocyanate	91-08-7	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. Immediate medical treatment necessary.
Skin contact:	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Do not induce vomiting, seek medical advice immediately.
Symptoms:	See Section 11.
Notes to physician:	An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate. Treatment based on judgement of the physician in response to reactions of the patient.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water fog. Foam Carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	None known.
Hazardous combustion products:	Nitrous gases Irritating fumes. Isocyanate vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not empty into drains / surface water / ground water.
-----------------------------------	--

Clean-up methods:

Ensure adequate ventilation. Scrape up spilled material and place in a closed container for disposal. Wear suitable protective clothing, gloves and eye/face protection.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Wash thoroughly after handling. Protect from moisture. Use only with adequate ventilation.

Storage:

For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F). Avoid moisture. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m3) PEL	None	None
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Toluene-2,6-diisocyanate	0.005 ppm STEL Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor. 0.001 ppm TWA Inhalable fraction and vapor. (Dermal sensitization) (Respiratory sensitization)	None	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate.

Eye/face protection:

Safety glasses with side-shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Light Grey
Odor:	Slight
Odor threshold:	Not available.
pH:	Neutral
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not applicable
Specific gravity:	1.15
Vapor density:	Not available.
Flash point:	Does not flash.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	None expected.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	2.89 %; 33 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Contact with moisture, other materials that react with isocyanates, or temperatures above 350° F (177° C), may cause polymerization.
Hazardous decomposition products:	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides. carbon monoxide Hydrogen cyanide.
Incompatible materials:	Oxidizing agents. Alcohols. Water. Strong bases.
Reactivity:	Not available.
Conditions to avoid:	Avoid moisture. Prolonged exposure to heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Inhalation, Skin, Eyes, Ingestion
------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. Dryness of nasal passages, sore throat, cough, tightness of chest, shortness of breath. Persons suffering from allergic reactions to isocyanates should avoid contact with the product. This product may cause sensitization by inhalation and skin contact. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. May cause respiratory tract irritation.
Skin contact:	Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals. This product may discolor the skin.
Eye contact:	Contact with eyes will cause irritation.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Calcium oxide	None	Irritant, Corrosive, Eyes
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Toluene-2,6-diisocyanate	None	Allergen, Bone Marrow, Corrosive, Eyes, Irritant, Mutagen, Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No
Talc	No	Group 2B	No
Calcium oxide	No	No	No
Titanium dioxide	No	Group 2B	No
Toluene-2,6-diisocyanate	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of Ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	Toluene-2,6-diisocyanate (CAS# 91-08-7).
CERCLA/SARA Section 302 EHS:	Toluene-2,6-diisocyanate (CAS# 91-08-7).
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene-2,6-diisocyanate (CAS# 91-08-7).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 8, 9, 15

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 08/31/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.